

PLATINUM

822U-016 S3S FO SR

STANDARD EN ISO 20345:2022 + A1:2024

SIZES 35-47



A - Antistatic



PS- Anti-perforation insert



Toecap resistant up to an impact of 200 joules and crushing of 15 KN



E - Energy absorption in the heel region



FO - Sole resistant to hydrocarbons



WPA -Upper resistant to water penetration and absorption



SR -Slip resistance on ceramic tile with glycerin



Metal free

Three-dimensional **SPYDER-NET**: lining with moisture absorption and release properties. Its special three-dimensional structure provides exceptional shape memory and high snag-

Reflective material

Dual density **TYRE** sole designed to offer maximum flexibility and lightness

High-visibility fabric resistant to water penetration and absorption

VELOURTECH soft suede leather upper, resistant to water penetration and absorption

Ultralight and flexible **TYRE PU/PU** sole thanks to Smart Injection: this special technology combines the mold construction with the injection process of the PU Esolight 2.0 compound and allows to achieve different PU-densities guaranteeing lightness, flexibility and durability



TYRE dual density PU/PU

- Resistant to hydrocarbons
- Excellent abrasion resistance
- Lugged sole for better grip on stairs
- Antistatic sole
- Sole profiling for maximum ground grip
- Lightness and comfort thanks to Smart Injection

PZ88 fiberglass toe cap and **TXZERO STRONG** anti puncture insole made of high tenacity fibers to obtain a flexible textile that adapts to the movement of the foot; it is intrinsically antistatic



HIB/IC

- Anatomico
- Tessuto in poliestere microforato = massima traspirabilità
- Celle ad alveare per assorbimento urti e traspirabilità