HEIMDALL

203BB-02 S7S SC FO LG SR

STANDARD EN ISO 20345:2022+A1:2024 **SIZES 37-47**

Breathable and water-resistant GORE-TEX Performance Comfort Footwear membrane: it allows the natural foot thermoregulation providing unparalleled comfort and water-resistance

Reflective material

Dual density ICON PU/PU sole designed to offer maximum comfort, slip resistance, excellent performances across all terrains, from wet to dry conditions. It has been tested in SATRA laboratories to resist slipping on metal grates (Kennedy Grating Test) and wooden boards (Scaffold Board Test)





A - Antistatic



PS – Anti-perforation insert



E – Energy absorption in the heel region



FO - Sole resistant to hydrocarbons



Toecap resistant up to an impact of 200 joules and crushing of 15 KN



SC - abrasion resistant overcap



WR -Water-resistant footwear



WPA –Upper resistant to water penetration and absorption



LG - ladder grip system

Esolight 1.0 polyurethane midsole. The low-density

comfort and lightness



SR -Slip resistance on ceramic tile with



Dual density ICON PU/PU

- Resistant to hydrocarbons
- Antistatic sole (A)
- Non-slip sole suitable for use on metal and wooden grates - SATRA Tests
- Self-cleaning profile to ensure maximum ground grip
- Wide fit for maximum stability and protection
- Shock-absorbing heel

PZX fiberglass toe cap and TXZERO STRONG anti puncture insole made of high tenacity fibers to obtain a flexible texile that adapts to the movement of the foot; it is intrinsically antistatic







T-01

- Anatomical insole for increased comfort
- High-density foam = energy absorption and rebound
- Lining made from conductive micro-perforated fabric to reduce wear and tear