

## BELMONT

### 258P-001 S3 HI HRO SRC

STANDARD EN ISO 20345:2011

SIZES 38-48



Three-dimensional **SPYDER-NET**: lining with moisture absorption and release properties. Its special three-dimensional structure provides exceptional shape memory and high snag-resistance

Reflective material

Bi-component **HYBRID PU/RUBBER** polyurethane and rubber sole, designed to provide maximum performance in terms of safety and comfort. The sole has been tested in SATRA laboratories for slip resistance on metal grates and wooden boards



#### Bi-component HYBRID PU/RUBBER

- Resistant to hydrocarbons
- Self-cleaning and enhanced lugs for maximum ground grip
- Non-slip sole suitable for use on metal and wooden grates - SATRA Tests
- Antistatic sole
- Rubber HRO tread heat-resistant

Leather reinforcement on the foot front to protect from splashes of molten metal

Velcro close-up and quick release lacing system

Water resistant leather upper

Esolight 1.0 polyurethane midsole. The low-density polyurethane microcells enhance energy absorption ensuring comfort and lightness

**COMPO200** composite toe cap and **TXZERO** multi-layer textile anti-puncture insole for exceptional lightness, protection and flexibility



#### H-01

- Shock absorption cell
- Breathable and antistatic
- Anatomical insole for higher comfort

