

NEXUS

259P-001 S3 M HI HRO SRC

STANDARD EN ISO 20345:2011

SIZES 38-48



Three-dimensional **SPYDER-NET**: lining with moisture absorption and release properties. Its special three-dimensional structure provides exceptional shape memory and high snag-resistance

Extra comfortable collar

Reflective material

Bi-component **HYBRID PU/RUBBER** polyurethane and rubber sole, designed to provide maximum performance in terms of safety and comfort. The sole has been tested in SATRA laboratories for slip resistance on metal grates and wooden boards



Bi-component HYBRID PU/RUBBER

- Resistant to hydrocarbons
- Self-cleaning and enhanced lugs for maximum ground grip
- Non-slip sole suitable for use on metal and wooden grates - SATRA Tests
- Antistatic sole
- Rubber HRO tread heat-resistant

Quick release closing system

TPU metatarsal protection certified according to the European Standard; it protects the foot from shocks and impacts

Water resistant leather upper



A - Antistatic



P - Anti-perforation insert



E - Energy absorption in the heel region



Sole resistant to hydrocarbons



Toecap resistant up to an impact of 200 joules and crushing of 15 KN



HRO - Heat-resistance by contact of the sole



HI - Heat insulation of the sole



WRU - Upper resistance to water penetration and absorption



M - Metatarsal protection

Esolight 1.0 polyurethane midsole. The low-density polyurethane microcells enhance energy absorption ensuring comfort and lightness

COMPO200 composite toe cap and **TXZERO** multi-layer textile anti-puncture insole for exceptional lightness, protection and flexibility



H-01

- Shock absorption cell
- Breathable and antistatic
- Anatomical insole for higher comfort