

PYTHON

269U-003 S3S FO SR

STANDARD EN ISO 20345:2022

SIZES 35-49



X-LEATHER



SMART INJECTION



ALU 200



TX ZERO STRONG



A - Antistatic



PS - Non-metal anti-perforation insert (truncated cone nail)



E - Energy absorption in the heel region



FO - Sole resistant to hydrocarbons



Toecap resistant up to an impact of 200 joules and crushing of 15 KN



SR - Slip resistance on ceramic tile with glycerin



WPA - Upper resistant to water penetration and absorption

Three-dimensional **SPYDER-NET**: lining with moisture absorption and release properties. Its special three-dimensional structure provides exceptional shape memory and high snag-resistance

Soft Lycra collar

Breathable and anti-abrasion technical fabric

Bi-component **TYRE PU-TPU** sole designed to offer maximum flexibility and durability. The thermoplastic outsole ensures remarkable mechanical features without affecting lightness and abrasion resistance

X-LEATHER multi-layer polyurethane reinforced material with high abrasion resistance properties and excellent water and oil resistance

Ultralight and flexible sole thanks to Smart Injection: this special technology combines the mold construction with the injection process of the PU Esolight 2.0 compound and allows to achieve different PU-densities guaranteeing lightness, flexibility and durability



ALU200 aluminium toe cap and **TXZERO STRONG** anti puncture insole made of high tenacity fibers to obtain a flexible textile that adapts to the movement of the foot; it is intrinsically antistatic



B-01

TYRE dual density PU/TPU

- High-density design to ensure maximum ground support
- Long flow channels for excellent sole cleaning
- Uniform heel lugs to ensure an efficient cushioning effect

- Anatomical insole made of polyurethane compound for improved comfort
- TPE charge system for an even distribution of energy
- Lining with through-holes to increase air circulation