## **INDIAN COBRA**

## 269U-009 S1PS FO SR

STANDARD EN ISO 20345:2022 SIZES 35-49

Three-dimensional SPYDER-NET: lining with moisture absorption and release properties. Its special three-dimensional structure provides exceptional shape memory and high snagresistance

Bi-component TYRE PU-TPU sole designed to offer maximum flexibility and durability. The thermoplastic outsole ensures remarkable mechanical features without affecting lightness and abrasion resistance



## TYRE bicomponente PU/TPU

- High-density design to ensure maximum ground support
- Long flow channels for excellent sole cleaning
- Uniform heel lugs to ensure an efficient cushioning effect













A - Antistatic



PS – Non-metal anti-perforation insert (truncated cone nail)



E – Energy absorption in the heel region



FO – Sole resistant to hydrocarbons



Toecap resistant up to an impact of 200 joules and crushing of 15 KN



SR -Slip resistance on ceramic tile with



X-LEATHER multi-layer polyurethane reinforced material with high abrasion resistance properties and excellent water and oil resistance

and breathable

Ultralight and flexible sole thanks to Smart Injection: this special technology combines the mold construction with the injection process of the PU Esolight 2.0 compound and allows to achieve different PU-densities guaranteeing lightness, flexibility and durability

ALU200 aluminium toe cap and TXZERO STRONG anti puncture insole made of high tenacity fibers to obtain a flexible texile that adapts to the movement of the foot; it is intrinsically antistatic







## B-01

- Anatomical insole made of polyurethane compound for improved comfort
- TPE charge system for an even distribution
- Lining with through-holes to increase air circulation