



VEGA

142UV-02 S3 ESD HRO SRC
 Standard EN ISO 20345:2011
 Sizes 36 - 47

SBX SYSTEM TPU stabilizer provides a high protection of the ankle and ensures perfect balance control while walking.

Three-dimensional Spyder-net lining: high performance tight-knit three-dimensional structure textile gives an exceptional comfort and keeps the feet dry.









Full grain Supremoil leather with high water repellence properties.

Maximum performance, comfort and durability with Tyre PU-Vibram® Rubber outsoles SRC HRO.



PZ88 Fiberglass toe cap (200 Joule) and perforation resistant Txzero insole made of ultimate textile material, offering outstanding lightness, protection and flexibility.



-  SRC Slip resistant
-  A Antistatic
-  P Perforation resistance
-  Resistant to 200 joules
-  E Energy Absorption of seat region
-  FO Fuel oil resistant sole
-  WRU Water penetration upper
-  HRO Heat-resistant outsole

The midsole is made of the special microcell compound **Esolight 1.0** that provides an excellent energy absorption. Esolight 1.0 provides a correct distribution of the body weight and impacts during walking, thus reducing the stress on the joints.

Outsole TYRE PU/RUBBER

- Vibram® rubber outsole HRO heat resistant.
- Thin rubber bottom to optimize lightness / durability ratio.
- Cleated profile for highest grip to the ground.
- FO Fuel resistance.
- Excellent abrasion resistance.

Tyre · T-01

- Anatomic footbed for improved comfort.
- Diversified zones with cushioning effect.
- Conductive lining to reduce foam wearing.
- High density foam = Support and shock absorption.

