



MANAUS

169UV-02 S3 WR HRO SRC
 Standard EN ISO 20345:2011
 Sizes 36 - 47



Waterproof GORE-TEX elastic membrane extremely breathable and water-repellent: comfort and resistance to water penetration.

Maximum performance, comfort and durability with Tyre PU-Vibram® Rubber outsole SRC HRO.



Outsole TYRE PU/RUBBER

- Vibram® rubber outsole HRO heat resistant.
- Thin rubber bottom to optimize lightness / durability ratio.
- Cleated profile for highest grip to the ground.
- FO Fuel resistance.
- Excellent abrasion resistance.

X-Weave high tenacity breathable nylon with differentiated zones. Extremely flexible, breathable, resistant to tearing and abrasion.



Easy-Fit system for perfect comfort.



PZ88 Fiberglass toe cap (200 Joule) and perforation resistant Txzero insole made of ultimate textile material, offering outstanding lightness, protection and flexibility.



- SRC** Slip resistant
- A** Antistatic
- P** Perforation resistance
- Resistant to 200 joules
- E** Energy Absorption of seat region
- FO** Fuel oil resistant sole
- WRU** Water penetration upper
- HRO** Heat-resistant outsole
- WR** Water resistance

The midsole is made of the special microcell compound Esolight 1.0 that provides an excellent energy absorption. Esolight 1.0 provides a correct distribution of the body weight and impacts during walking, thus reducing the stress on the joints.

Tyre · T-01

- Anatomic footbed for improved comfort.
- Diversified zones with cushioning effect.
- Conductive lining to reduce foam wearing.
- High density foam = Support and shock absorption.

