



## MORGAN

**172BB-01 S3 ESD SRC**

Standard EN ISO 20345:2011

Sizes 37 - 47

Three-dimensional Spyder-net lining: high performance tight-knit three-dimensional structure textile gives an exceptional comfort and keeps the feet dry.

Double density polyurethane sole Icon PU/PU: utmost slip resistant sole designed to provide excellent all-round performances.



### Outsole ICON PU/PU

- SRC Slip resistant outsole
- FO Fuel resistance
- Wide fit for maximum strength and protection
- Grip on ladders
- Shock absorption cell



PU and water resistant Tx-Micro upper with overwelding technology. Seamless technology to bind different materials of the upper without any stitching, but with a high-frequency welding.

Tx-Micro upper: technical textile, with the support of a strong, durable and extremely breathable microfiber.



**SRC** Slip resistant



**A** Antistatic



**P** Perforation resistance



Resistant to 200 joules



**E** Energy Absorption of seat region



**FO** Fuel oil resistant sole



**WRU** Water penetration upper

X-Leather on toe: material finished with a multi-layer of polyurethane compound.

The midsole is made of the special microcell compound Esolight 1.0 that provides an excellent energy absorption. The outsole is made of the Esolight 2.0 compound, for high durability and slip resistance.



PZX Fiberglass toe cap (200 Joule) and perforation resistant Txzero insole made of ultimate textile material, offering outstanding lightness, protection and flexibility.



### Icon · I-01

- Anatomic footbed made of open cell polyurethane foam
- Shock absorption area
- Extremely breathable
- Antibacterial Foam