



ASGARD

204BB-03 S3 WR CI SRC

Standard EN ISO 20345:2011

DGUV 112-191

Sizes 37-47

Thinsulate® B200 is a lightweight and thin lining material for outstanding thermal insulation, that keeps the feet warm in extreme weather conditions.

Reflective material.

ICON dual density polyurethane sole designed for excellent performance on wettest and driest grounds. This sole has been tested for slip-resistance in the SATRA laboratories on metal grating and wood scaffold board.



ICON DUAL DENSITY PU

- SRC Slip resistance sole.
- Self-cleaning cleated sole
- Fuel oil resistance sole
- Wide fit for maximum stability and protection.
- Shock absorbing heel.



Calf leather

GORE-TEX membrane offers high climate comfort in all working conditions and provides durable waterproofness and high breathability.

Ultimate full grain leather: high breathability and water resistance.

Esolight 1.0 polyurethane midsole with reinforced Over cap. The low-density micro-cell polyurethane increase energy absorption, while the outsole is made by high-density Esolight 2.0 polyurethane to guarantee durability and slip resistance.

PZX fiberglass toe cap and anti-puncture Txzero textile insert for extreme lightness, protection and flexibility.



T-01

- Anatomic insole for more comfort
- Supporting PU foam = Dissipation and Energy Return
- Fully lined with conductive micro-perforated fabric to reduce foam wearing



	SRC Slip resistance
	A Antistatic
	P Perforation resistance
	Resistant to an impact of 200 Joules and compression of 15Kn
	E Energy absorption at the heel part
	FO Fuel oil resistance sole
	WRU Water penetration resistant upper
	CI Cold insulation of the sole
	WR Water resistance