



## AXEL

142U-003 S3 ESD SRC

Standard EN ISO 20345:2011

DGUV 112-191

Sizes 36-47



Three-dimensional Spyder-Net lining with moisture absorption and release properties. Its special three-dimensional and non-deformable textile structure ensures lasting comfort, breathability and elasticity.

The SBX TPU stabilizer is designed to hold the ankle and ensure perfect balance control while walking. This provides stability, comfort and protection on irregular surfaces.

TYRE dual density PU guaranties excellent flexibility and lightness.



### TYRE PU DUAL DENSITY

- SRC Slip resistance sole.
- Fuel oil resistance sole (FO)
- Smart Injection technology
- Excellent abrasion resistance



Upper made of suede Microtech microfiber extremely breathable and high-tensile, consists of nylon fibers combined with PU through a coagulation process. This provides extended durability, tear and bending strength.

Ultra-light and flexible sole with Smart Injection: a special technology that, through the combination of a peculiar mold build-up and the injection of PU Esolight 2.0 compound, provides for different densities and at the same time guaranties lightness, flexibility and durability.

PZ88 fiberglass toe cap and anti-puncture Txzero textile insert for extreme lightness, protection and flexibility.



### T-01

- Anatomic insole for more comfort
- Supporting PU foam = Dissipation and Energy Return
- Fully lined with conductive micro-perforated fabric to reduce foam wearing

