




CHILE

169U-014 S1P ESD SRC

Standard EN ISO 20345:2011

DGUV 112-191

Sizes 36-47



Three-dimensional Spyder-Net lining with moisture absorption and release properties. Its special three-dimensional and non-deformable textile structure ensures lasting comfort, breathability and elasticity.

TYRE dual density PU guaranties excellent flexibility and lightness.



TYRE PU DUAL DENSITY

- SRC Slip resistance sole.
- Fuel oil resistance sole (FO)
- Smart Injection technology
- Excellent abrasion resistance

Extra comfortable collar in lycra.

Easy-fit system for perfect comfort.

X-Weave nylon is a one-piece upper with different textures for different functional areas. Extremely flexible, breathable, tearing and abrasion resistant.

Ultra-light and flexible sole with Smart Injection: a special technology that, through the combination of a peculiar mold build-up and the injection of PU Esolight 2.0 compound, provides for different densities and at the same time guaranties lightness, flexibility and durability.

PZ88 fiberglass toe cap and anti-puncture Txzero textile insert for extreme lightness, protection and flexibility.



T-01

- Anatomic insole for more comfort
- Supporting PU foam = Dissipation and Energy Return
- Fully lined with conductive micro-perforated fabric to reduce foam wearing