



## ESTORIL

221U-002 S2 ESD SRC

Standard EN ISO 20345:2011

Sizes 36-47



	SRC Slip resistance
	A Antistatic
	Resistant to an impact of 200 Joules and compression of 15Kn
	E Energy absorption at the heel part
	FO Fuel oil resistance sole
	WRU Water penetration resistant upper

Three-dimensional Spyder-Net lining with moisture absorption and release properties. Its special three-dimensional and non-deformable textile structure ensures lasting comfort, breathability and elasticity.

TYRE dual density PU guaranties excellent flexibility and lightness.



### TYRE PU DUAL DENSITY

- SRC Slip resistance sole.
- Fuel oil resistance sole (FO)
- Smart Injection technology
- Excellent abrasion resistance

Extra comfortable Lycra collar and tongue.

Upper made of Microtech microfiber extremely breathable and high-tensile, consists of nylon fibers combined with PU through a coagulation process. This provides extended durability, tear and bending strength.

Ultra-light and flexible sole with Smart Injection: a special technology that, through the combination of a peculiar mold build-up and the injection of PU Esolight 2.0 compound, provides for different densities and at the same time guaranties lightness, flexibility and durability.

PZ88 fiberglass toe cap for maximum mechanical performance, in compliance with EN 12568 requirements. Light, non-magnetic and lasting protection in all conditions.



### T-01

- Anatomic insole for more comfort
- Supporting PU foam = Dissipation and Energy Return
- Fully lined with conductive micro-perforated fabric to reduce foam wearing

