



FUJI

221U-001 S2 ESD SRC

Standard EN ISO 20345:2011

Sizes 36-47



	SRC Slip resistance
	A Antistatic
	Resistant to an impact of 200 Joules and compression of 15Kn
	E Energy absorption at the heel part
	FO Fuel oil resistance sole
	WRU Water penetration resistant upper

Three-dimensional Spyder-Net lining with moisture absorption and release properties. Its special three-dimensional and non-deformable textile structure ensures lasting comfort, breathability and elasticity.


TYRE dual density PU guaranties excellent flexibility and lightness.



TYRE PU DUAL DENSITY

- SRC Slip resistance sole.
- Fuel oil resistance sole (FO)
- Smart Injection technology
- Excellent abrasion resistance

PZ88 fiberglass toe cap for maximum mechanical performance, in compliance with EN 12568 requirements. Light, non-magnetic and lasting protection in all conditions.



Extra comfortable Lycra collar and tongue.

Upper made of Microtech microfiber extremely breathable and high-tensile, consists of nylon fibers combined with PU through a coagulation process. This provides extended durability, tear and bending

Ultra-light and flexible sole with Smart Injection: a special technology that, through the combination of a peculiar mold build-up and the injection of PU Esolight 2.0 compound, provides for different densities and at the same time guaranties lightness, flexibility and durability.



T-01

- Anatomic insole for more comfort
- Supporting PU foam = Dissipation and Energy Return
- Fully lined with conductive micro-perforated fabric to reduce foam wearing