



GHIBLI

246U-002 S3 SRC

Standard EN ISO 20345:2011

Sizes 35-48



SMART INJECTION TXZERO



Three-dimensional Spyder-Net lining with moisture absorption and release properties. Its special three-dimensional and non-deformable textile structure ensures lasting comfort, breathability and elasticity.

TYRE dual density PU guaranties excellent flexibility and lightness.



TYRE PU DUAL DENSITY

- SRC Slip resistance sole.
- Fuel oil resistance sole (FO)
- Smart Injection technology
- Excellent abrasion resistance



Pu Tek upper fabric with incomparable abrasion resistance: over 1 million cycles in humid condition compared to the 51.200 cycles required by the European Rule, despite preserving its performance in flexibility, lightness, breathability and water resistance.

Ultra-light and flexible sole with Smart Injection: a special technology that, through the combination of a peculiar mold build-up and the injection of PU Esolight 2.0 compound, provides for different densities and at the same time guaranties lightness, flexibility and durability.

Alu200 aluminum toe cap and anti-puncture Txzero textile insert for extreme lightness, protection and flexibility.



T-01

- Anatomic insole for more comfort
- Supporting PU foam = Dissipation and Energy Return
- Fully lined with conductive micro-perforated fabric to reduce foam wearing



SRC Slip resistance



A Antistatic



P Perforation resistance



Resistant to an impact of 200 Joules and compression of 15Kn



E Energy absorption at the heel part



FO Fuel oil resistance sole



WRU Water penetration resistant upper