



JARAMA

164U-018 S3 ESD SRC

Standard EN ISO 20345:2011

DGUV 112-191

Sizes 36-47



Three-dimensional Spyder-Net lining with moisture absorption and release properties. Its special three-dimensional and non-deformable textile structure ensures lasting comfort, breathability and elasticity.

TYRE dual density PU guaranties excellent flexibility and lightness.



TYRE PU DUAL DENSITY

- SRC Slip resistance sole.
- Fuel oil resistance sole (FO)
- Smart Injection technology
- Excellent abrasion resistance



Upper made of Microtech microfiber extremely breathable and high-tensile, consists of nylon fibers combined with PU through a coagulation process. This provides extended durability, tear and bending strength.

PZ88 fiberglass toe cap and anti-puncture Txzero textile insert for extreme lightness, protection and flexibility.



Ultra-light and flexible sole with Smart Injection: a special technology that, through the combination of a peculiar mold build-up and the injection of PU Esolight 2.0 compound, provides for different densities and at the same time guaranties lightness, flexibility and durability.



T-01

- Anatomic insole for more comfort
- Supporting PU foam – Dissipation and Energy Return
- Fully lined with conductive micro-perforated fabric to reduce foam wearing



SRC Slip resistance



A Antistatic



P Perforation resistance



Resistant to an impact of 200 Joules and compression of 15Kn



E Energy absorption at the heel part



FO Fuel oil resistance sole



WRU Water penetration resistant upper