



MANAUS

169UV-02 S3 WR HRO SRC

Standard EN ISO 20345:2011

Sizes 36-47



GORE-TEX membrane offers high climate comfort in all working conditions and provides durable waterproofness and high breathability.

Two-component TYRE PU-RUBBER VIBRAM® sole. The S-Line design facilitates movements while walking and the optimized cleated profile guarantees lightness and durability.



TYRE PU-RUBBER VIBRAM®

- Rubber Vibram® Outsole HRO
- High slip resistance
- Excellent abrasion resistance
- Optimized cleated profile to guarantee lightness and durability



Easy-fit system for perfect comfort.

X-Weave nylon is a one-piece upper with different textures for different functional areas. Extremely flexible, breathable, tearing and abrasion resistant.

The Esolight 1.0 polyurethane midsole made of low-density micro-cells increases energy absorption and provides a correct body weight distribution while walking.

PZ88 fiberglass toe cap and anti-puncture Txzero textile insert for extreme lightness, protection and flexibility.



T-01

- Anatomic insole for more comfort
- Supporting PU foam – Dissipation and Energy Return
- Fully lined with conductive micro-perforated fabric to reduce foam wearing

	SRC Slip resistance
	A Antistatic
	P Perforation resistance
	Resistant to an impact of 200 Joules and compression of 15Kn
	E Energy absorption at the heel part
	FO Fuel oil resistance sole
	WRU Water penetration resistant upper
	HRO Heat resistant outsole
	WR Water resistance