



MENDOZA

131BB-05 S3 SRC

Standard EN ISO 20345:2011

DGUV 112-191

Sizes 37-47

The tunnel loops guarantee a quick and easy fit.

Maximum stability and durability thanks to TPU protective element in the heel area.

ICON dual density polyurethane sole designed for excellent performance on wettest and driest grounds. This sole has been tested for slip-resistance in the SATRA laboratories on metal grating (Kennedy Grating Test) and wood scaffold board (Scaffold Board Test).



DUAL DENSITY PU ICON

- SRC Slip resistance sole.
- Self-cleaning cleated sole
- Fuel oil resistance sole
- Wide fit for maximum stability and protection.



Unlined for maximum breathability

Full grain Idrotech leather with high water resistance properties.

Esolight 1.0 polyurethane midsole with reinforced Over cap. The low-density micro-cell polyurethane increase energy absorption, while the outsole is made by high-density Esolight polyurethane to guarantee durability and slip resistance.

PZX fiberglass toe cap and anti-puncture Txzero textile insert for extreme lightness, protection and flexibility.



SRC Slip resistance

A Antistatic

P Perforation resistance

Resistant to an impact of 200 Joules and compression of 15Kn

E Energy absorption at the heel part

FO Fuel oil resistance sole

WRU Water penetration resistant upper

T-01

- Anatomic insole for more comfort
- Supporting PU foam – Dissipation and Energy Return
- Fully lined with conductive micro-perforated fabric to reduce foam wearing

