



MORGAN

172BB-01 S3 ESD SRC

Standard EN ISO 20345:2011

Sizes 37-47



Three-dimensional Spider-Net lining with moisture absorption and release properties. Its special three-dimensional and non-deformable textile structure ensures lasting comfort, breathability and elasticity.

ICON dual density polyurethane sole designed for excellent performance on wettest and driest grounds. This sole has been tested for slip-resistance in the SATRA laboratories on metal grating (Kennedy Grating Test) and wood scaffold board (Scaffold Board Test).



DUAL DENSITY PU ICON

- SRC Slip resistance sole.
- Self-cleaning cleated sole
- Fuel oil resistance sole
- Wide fit for maximum stability and protection.



Upper in PU and Tx-Micro fabric joined with Overwelding technology, a process that allows to combine different materials thanks to the high frequency welding.

Tx-Micro: technical fabric combined with a resistant and breathable microfiber. An innovative material that gives a sporty look with the same performance as leather in terms of tear resistance and comfort.

X-Leather, leather upper material reinforced with polyurethane multi-layer, high abrasion resistant.

The Esolight 1.0 midsole is made of lower density micro-cell polyurethane so to increase energy absorption, while the outsole is made by high-density Esolight polyurethane to guarantee durability and slip resistance.

PZX fiberglass toe cap and anti-puncture Txzero textile insert for extreme lightness, protection and flexibility.



T-01

- Anatomic insole for more comfort
- Supporting PU foam – Dissipation and Energy Return
- Fully lined with conductive micro-perforated fabric to reduce foam wearing

	SRC Slip resistance
	A Antistatic
	P Perforation resistance
	Resistant to an impact of 200 Joules and compression of 15Kn
	E Energy absorption at the heel part
	FO Fuel oil resistance sole
	WRU Water penetration resistant upper