



SANTIAGO

169UV-13 S3 ESD HRO SRC

Standard EN ISO 20345:2011

Sizes 36-47



Three-dimensional Spyder-Net lining with moisture absorption and release properties. Its special three-dimensional and non-deformable textile structure ensures lasting comfort, breathability and elasticity.

Two-component TYRE PU-RUBBER VIBRAM® sole. The S-Line design facilitates movements while walking and the optimized cleated profile guarantees lightness and durability



Easy-fit system for perfect comfort.

X-Weave nylon is a one-piece upper with different textures for different functional areas. Extremely flexible, breathable, tearing and abrasion resistant.

The Esolight 1.0 polyurethane midsole made of low-density micro-cells increases energy absorption and provides a correct body weight distribution while walking.

	SRC Slip resistance
	A Antistatic
	P Perforation resistance
	Resistant to an impact of 200 Joules and compression of 15Kn
	E Energy absorption at the heel part
	FO Fuel oil resistance sole
	WRU Water penetration resistant upper
	HRO Heat resistant outsole



TYRE PU-RUBBER VIBRAM®

- Outsole in Rubber Vibram® HRO
- High slip-resistance
- high abrasion resistance
- Optimized cleated profile to guarantee lightness and durability

PZ88 fiberglass toe cap and anti-puncture Txzero textile insert for extreme lightness, protection and flexibility.



T-01

- Anatomic insole for more comfort
- Supporting PU foam = Dissipation and Energy Return
- Fully lined with conductive micro-perforated fabric to reduce foam wearing