



SANTOS

172BB-06 S3 WR SRC

Standard EN ISO 20345:2011

Sizes 37-47



GORE-TEX membrane offers high climate comfort in all working conditions and provides durable waterproofness and high breathability.

ICON dual density polyurethane sole designed for excellent performance on wettest and driest grounds. This sole has been tested for slip-resistance in the SATRA laboratories on metal grating (Kennedy Grating Test) and wood scaffold board (Scaffold Board Test).



DUAL DENSITY PU ICON

- SRC Slip resistance sole.
- Self-cleaning cleated sole
- Fuel oil resistance sole
- Wide fit for maximum stability and protection.



Upper in PU and Tx-Micro fabric joined with Overwelding technology, a process that allows to combine different materials thanks to the high frequency welding.

Tx-Micro: technical fabric combined with a resistant and breathable microfiber. An innovative material that gives a sporty look with the same performance as leather in terms of tear resistance and comfort.

X-Leather, leather upper material reinforced with polyurethane multi-layer, high abrasion resistant.

Esolight 1.0 polyurethane midsole with reinforced Over cap. The low-density micro-cell polyurethane increase energy absorption, while the outsole is made by high-density Esolight polyurethane to guarantee durability and slip resistance.

PZX fiberglass toe cap and anti-puncture Txzero textile insert for extreme lightness, protection and flexibility.



T-01

- Anatomic insole for more comfort
- Supporting PU foam = Dissipation and Energy Return
- Fully lined with conductive micro-perforated fabric to reduce foam wearing

	SRC Slip resistance
	A Antistatic
	P Perforation resistance
	Resistant to an impact of 200 Joules and compression of 15Kn
	E Energy absorption at the heel part
	FO Fuel oil resistance sole
	WRU Water penetration resistant upper
	WR Water resistance