



## VEGA

142UV-02 S3 ESD HRO SRC

Standard EN ISO 20345:2011

Sizes 36-47

Three-dimensional Spyder-Net lining with moisture absorption and release properties. Its special three-dimensional and non-deformable textile structure ensures lasting comfort, breathability and elasticity.

Supremoil full grain leather with water resistance and breathability properties.

Two-component TYRE PU-RUBBER VIBRAM® sole. The S-Line design facilitates movements while walking and the optimized cleated profile guarantees lightness and durability



### TYRE PU-GOMMA VIBRAM®

- Outsole in Rubber Vibram® HRO
- High slip-resistance
- High abrasion resistance
- Optimized cleated profile to guarantee lightness and durability



The SBX TPU stabilizer is designed to hold the ankle and ensure perfect balance control while walking. This provides stability, comfort and protection on irregular surfaces.

PZ88 fiberglass toe cap and anti-puncture Txzero textile insert for extreme lightness, protection and flexibility.



	SRC Slip resistance
	A Antistatic
	P Perforation resistance
	Resistant to an impact of 200 Joules and compression of 15Kn
	E Energy absorption at the heel part
	FO Fuel oil resistance sole
	WRU Water penetration resistant upper
	HRO Heat resistant outsole

Ultra-light and flexible sole with Smart Injection: a special technology that, through the combination of a peculiar mold build-up and the injection of PU Esolight 2.0 compound, provides for different densities and at the same time guarantees lightness, flexibility and durability.



### T-01

- Anatomic insole for more comfort
- Supporting PU foam = Dissipation and Energy Return
- Fully lined with conductive micro-perforated fabric to reduce foam wearing