



## VIKING

127BV-04 S3 WR CI HI HRO SRC

Standard EN ISO 20345:2011

Sizes 38-48

Breathable and water-resistant GORE-TEX membrane and Thinsulate® B600 highly insulated lining.

Maximum stability and durability thanks to TPU protective element in the heel area.

Two-component ICON PU-RUBBER VIBRAM® FIRE&ICE sole developed to provide grip and stability, to withstand low and high temperatures. Slip-resistance sole tested to the SATRA laboratories on metal grating and wooden scaffold boards.



Pelle di vitello.

Zip with gusset.

Reflective material.

Ultimate full grain leather: high breathability and water resistance.

Esolight 1.0 polyurethane midsole with reinforced Over cap. The low-density micro-cell polyurethane increase energy absorption ensuring comfort and lightness.



	SRC Slip resistance
	A Antistatic
	P Perforation resistance
	Resistant to an impact of 200 Joules and compression of 15Kn
	E Energy absorption at the heel part
	FO Fuel oil resistance sole
	WRU Water penetration resistant upper
	HI Heat insulation of the sole
	CI Cold insulation of the sole
	HRO Heat resistant outsole
	WR Water resistance



### ICON PU-RUBBER VIBRAM® FIRE&ICE

- Outsole in Rubber Vibram® Fire&Ice
- Flexibility and traction down to -23°C
- Designed for the use with crampons
- High slip resistance with cold

PZX fiberglass toe cap and anti-puncture Txzero textile insert for extreme lightness, protection and flexibility.



### I-01

- Shock absorbing insert
- Anatomic insole for higher comfort
- Aluminium foil = thermal refraction