









MALBEK

610Z-023 S1P SRC

Standard EN ISO 20345:2011

Sizes 36-47



-  SRC Slip resistance
-  A Antistatic
-  P Perforation resistance
-  Resistant to an impact of 200 Joules and compression of 15Kn
-  E Energy absorption at the heel part
-  FO Fuel oil resistance sole

Three-dimensional Spyder-Net lining with moisture absorption and release properties. Its special three-dimensional and non-deformable textile structure ensures lasting comfort, breathability and elasticity.

SOLID dual density PU guaranties excellent comfort and lightness.



SOLID PU DUAL DENSITY

- SRC Slip resistance sole.
- Fuel oil resistance sole (FO)
- Esolight 1.0+2.0 compound
- Excellent abrasion resistance
- Shock absorbing heel



Soft Velourtech suede leather: maximum lightness and extreme breathability.

Exclusive super flexible system made of dual density polyurethane Esolight 1.0 + 2.0. The Esolight 1.0 midsole is made of lower density micro-cell polyurethane so to increase energy absorption, while the outsole is made by high-density Esolight 2.0 polyurethane to guarantee durability and slip resistance.

Inox steel toecap and anti-puncture for high level of protection.



S-01

- Ultralight
- High abrasion resistant fabric Tessuto ad alta resistenza all'abrasione
- Anatomic insole for better comfort