



RAGUSA FAST

969P-010 S3 M HI HRO SRC

Standard EN ISO 20345:2011

Sizes 38-48

Lining in soft polyester velvet-effect, for constant comfort.

Full grain Idrotech leather with high water resistance properties.

Reflective material.

Two-component HYBRID PU-RUBBER HRO sole, developed to offer maximum performance in terms of safety and comfort. Slip-resistance sole tested to the SATRA laboratories on metal grating and wooden scaffold boards.



HYBRID PU-RUBBER

- Rubber Outsole HRO
- Fuel oil resistance sole (FO)
- Self-cleaning cleated sole to ensure maximum adherence to the ground
- Excellent abrasion resistance



BOA® Fit System consists of a micro-adjustable dial, a super-strong lightweight lace and low friction lace guides; engineered for easy, accurate and safe adjustment.

Metatarsal protection in PORON: newest micro-cellular polyurethane, used to protect the body from shocks and impact, by discharging the impact energy and avoiding any injury to the protected area.

Maximum protection and durability thanks to TPU protective element applied in the front area.

Steel toe cap and anti-puncture Txzero textile insert for extreme protection, lightness and flexibility.



	SRC Slip resistance
	A Antistatic
	P Perforation resistance
	Resistant to an impact of 200 Joules and compression of 15Kn
	E Energy absorption at the heel part
	FO Fuel oil resistance sole
	WRU Water penetration resistant upper
	HI Heat insulation of the sole
	HRO Heat resistant outsole
	M Metatarsal protection

Esolight 1.0 polyurethane midsole with reinforced Over cap. The low-density micro-cell polyurethane increase energy absorption ensuring comfort and lightness.

T-01

- Anatomic insole for more comfort
- Supporting PU foam – Dissipation and Energy Return
- Fully lined with conductive micro-perforated fabric to reduce foam wearing

