



## ALLIGATOR

172BV-02 S3 WR CI HI HRO SRC

Standard EN ISO 20345:2011

Sizes 38-48



GORE-TEX membrane offers high climate comfort in all working conditions and provides durable waterproofness and high breathability.

Tx-Micro: technical fabric combined with a resistant and breathable microfiber. An innovative material that gives a sporty look with the same performance as leather in terms of tear resistance and comfort.

Two-component ICON PU-RUBBER VIBRAM® sole, guarantees maximum grip and stability on difficult uneven grounds. Slip-resistance sole tested to the SATRA laboratories on metal grating and wooden scaffold boards.



Upper in PU and Tx-Micro fabric joined with Overwelding technology, a process that allows to combine different materials thanks to the high frequency welding.

X-Leather, leather upper material reinforced with polyurethane multi-layer, high abrasion resistant.

	SRC Slip resistance
	A Antistatic
	P Perforation resistance
	Resistant to an impact of 200 Joules and compression of 15Kn
	E Energy absorption at the heel part
	FO Fuel oil resistance sole
	WRU Water penetration resistant upper
	HI Heat insulation of the sole
	CI Cold insulation of the sole
	HRO Heat resistant outsole
	WR Water resistance



### ICON PU-RUBBER VIBRAM®

- Outsole in Rubber Vibram® HRO
- Designed for the use with crampons
- High slip resistance
- Wide, profiled, slip-resistant waist area

PZX fiberglass toe cap and anti-puncture Txzero textile insert for extreme lightness, protection and flexibility.



Esolight 1.0 polyurethane midsole with reinforced Over cap. The low-density micro-cell polyurethane increase energy absorption ensuring comfort and lightness.



### T-01

- Anatomic insole for more comfort
- Supporting PU foam = Dissipation and Energy Return
- Fully lined with conductive micro-perforated fabric to reduce foam wearing