



## BASQUIAT

275S-002 S2 SRC

Standard EN ISO 20345:2011

Sizes 36-48



	SRC Slip resistance
	A Antistatic
	Resistant to an impact of 200 Joules and compression of 15Kn
	E Energy absorption at the heel part
	FO Fuel oil resistance sole
	WRU Water penetration resistant upper

Three-dimensional Spyder-Net lining with moisture absorption and release properties. Its special three-dimensional and non-deformable textile structure ensures lasting comfort, breathability and elasticity.

Water resistant upper made with synthetic material.

SOLID dual density PU guarantees excellent comfort and lightness.

The Esolight 1.0 midsole is made of lower density micro-cell polyurethane so to increase energy absorption, while the outsole is made by high-density Esolight 2.0 polyurethane to guarantee durability and slip resistance.



### SOLID PU DUAL DENSITY

- SRC Slip resistance sole.
- Fuel oil resistance sole (FO)
- Esolight 1.0+2.0 compound
- Excellent abrasion resistance
- Shock absorbing heel

COMPO200 polymeric toe cap: Resistant to an impact of 200 Joules according to European standards. Non-magnetic and light.



### S-02

- Antibacterial
- Perforated polyester fabric = maximum breathability Antibacterial
- Honeycomb design for shock absorption and breathability

