



CHALLENGE

981S-003 S3 SRC

Standard EN ISO 20345:2011

Sizes 36-48

ESOLIGHT TXZERO

COMPO 200

METAL FREE

Three-dimensional Spyder-Net lining with moisture absorption and release properties. Its special three-dimensional and non-deformable textile structure ensures lasting comfort, breathability and elasticity.

SOLID dual density PU guaranties excellent comfort and lightness.



SOLID PU DUAL DENSITY

- SRC Slip resistance sole.
- Fuel oil resistance sole (FO)
- Esolight 1.0+2.0 compound
- Excellent abrasion resistance
- Shock absorbing heel



Quick release lacing System.

Full grain Idrotech leather with high water resistance properties.

The Esolight 1.0 midsole is made of lower density micro-cell polyurethane so to increase energy absorption, while the outsole is made by high-density Esolight 2.0 polyurethane to guarantee durability and slip resistance.

COMPO200 polymeric toe cap anti-puncture Txzero textile insert for extreme lightness, protection and flexibility.



S-02

- Antibacterial
- Perforated polyester fabric = maximum breathability Antibacterial
- Honeycomb design for shock absorption and breathability

- SRC Slip resistance
- A Antistatic
- P Perforation resistance
- Resistant to an impact of 200 Joules and compression of 15Kn
- E Energy absorption at the heel part
- FO Fuel oil resistance sole
- WRU Water penetration resistant upper