



## LOTHAR

692Z-014 S3 SRC

Standard EN ISO 20345:2011

Sizes 36-47



|  |  |
|--|--|
|  | SRC Slip resistance  |
|  | A Antistatic   |
|  | P Perforation resistance                                     |
|  | Resistant to an impact of 200 Joules and compression of 15Kn |
|  | E Energy absorption at the heel part                         |
|  | FO Fuel oil resistance sole                                  |
|  | WRU Water penetration resistant upper                        |

Three-dimensional Spyder-Net lining with moisture absorption and release properties. Its special three-dimensional and non-deformable textile structure ensures lasting comfort, breathability and elasticity.

SOLID dual density PU guaranties excellent comfort and lightness.



High-visibility, water resistant fabric.

Reflective material.

Soft Velourtech suede leather: maximum lightness and extreme breathability.



### SOLID PU DUAL DENSITY

- SRC Slip resistance sole.
- Fuel oil resistance sole (FO)
- Esolight 1.0+2.0 compound
- Excellent abrasion resistance
- Shock absorbing heel

Steel toe cap (200 Joules) and anti-puncture Txzero textile insert for extreme protection.



Exclusive super flexible system made of dual density polyurethane Esolight 1.0 + 2.0. The Esolight 1.0 midsole is made of lower density micro-cell polyurethane so to increase energy absorption, while the outsole is made by high-density Esolight polyurethane to guarantee durability and slip resistance.

### S-01

- Ultralight
- High abrasion resistant Fabric
- Anatomic insole for better comfort