

MANAUS

169UV-02 S3 WR HRO SRC

Standard EN ISO 20345:2011

Sizes: 36-47



Antistaticity



Impact and compression resistance



Hydrocarbon resistant outsole



Puncture resistance



Energy absorption at the heel



Upper resistance to water penetration and absorption



Heat resistant outsole



Water resistance

Easy-fit system for perfect comfort.

GORE-TEX membrane offers high climate comfort in all working conditions and provides durable waterproofness and high breathability.

Two-component **Tyre Pu-Gomma Vibram®** sole. The S-Line design facilitates movements while walking and the optimized cleated profile guarantees lightness and durability

X-Weave nylon is a onepiece upper with different textures for different functional areas. Extremely flexible, breathable, tearing and abrasion resistant.

Toe cap reinforced with **TPU film** to provide greater durability.

PZ88 fiberglass toe cap and anti-puncture **Txzero** textile insert for extreme lightness, protection and flexibility.

The **Esolight 1.0** polyurethane midsole made of low-density micro-cells increases energy absorption and provides a correct body weight distribution while walking.

Sole TYRE PU-RUBBER VIBRAM®

- Outsole in Rubber Vibram® HRO
- Thin rubber bottom to optimize lightness
- SRC High slip-resistance
- Fuel oil resistance sole
- High abrasion resistance



T-01

- Anatomic insole for more comfort
- Supporting PU foam = Dissipation and Energy Return
- Fully lined with conductive micro-perforated fabric to reduce foam wearing