PezzoL

SONORA

916P-018 S3 HI HRO SRC

Standard EN ISO 20345:2011 Sizes 38-48

Three-dimensional Spyder-Net lining with moisture absorption and release properties. Its special three-dimensional and non-deformable textile structure ensures lasting comfort, breathability and elasticity.

The SBX TPU stabilizer is designed to hold the ankle and ensure perfect balance control while walking. This provides stability, comfort and protection on irregular surfaces.

Two-component HYBRID PU-RUBBER HRO sole, developed to offer maximum performance in terms of safety and comfort. Slip-resistance sole tested to the SATRA laboratories on metal grating and wooden scaffold boards.



HYBRID PU-RUBBER

- Rubber Outsole HRO
- Fuel oil resistance sole (FO)
- Self-cleaning cleated sole to ensure maximum adherence to the ground
- Excellent abrasion resistance
- Shock absorption cell





TPU protection elements applied on the

collar and in the front area to guarantee

protection from impacts and frictions.

Supremoil full grain leather with water

resistance and breathability properties.





SRC Slip resistance



A Antistatic



P Perforation resistance



Resistant to an impact of 200 Joules and compression of 15Kn



E Energy absorption at the heel part



FO Fuel oil resistance sole



WRU Water penetration resistant upper




HRO Heat resistant outsole



HI Heat insulation of the sole

The Esolight 1.0 polyurethane midsole made of low-density micro-cells increases energy absorption and provides a correct body weight distribution while walking.







T-01

- Anatomic insole for more comfort
- Supporting PU foam = Dissipation and **Energy Return**
- Fully lined with conductive microperforated fabric to reduce foam wearing