

WOLFGANG

981S-006 S3 ESD SRC

Standard EN ISO 20345:2011

Sizes: 36-48



ESOLIGHT **TXZERO**



Antistaticity



Impact and compression resistance



Hydrocarbon resistant outsole



Puncture resistance



Energy absorption at the heel



Upper resistance to water penetration and absorption

Three-dimensional **Spyder-Net** lining with moisture absorption and release properties. Its special three-dimensional and non-deformable textile structure ensures lasting comfort, breathability and elasticity.

Quick release lacing System.

Full grain **Idrotech** leather with high resistance to penetration and water absorption.

Solid dual density PU guaranties excellent comfort and lightness.

X-Leather, leather upper material reinforced with polyurethane multi-layer, high abrasion resistant.



Exclusive super flexible system made of dual density polyurethane **Esolight 1.0 + 2.0**. The Esolight 1.0 midsole is made of lower density micro-cell polyurethane so to increase energy absorption, while the outsole is made by high-density Esolight polyurethane to guarantee durability and slip resistance.

Compo200 polymeric toe cap anti-puncture **Txzero** textile insert for extreme lightness, protection and flexibility.

Sole SOLID PU DUAL DENSITY

- SRC Slip resistance sole
- Esolight 1.0+2.0 system
- Shock absorbing heel
- Fuel oil resistance sole
- Excellent abrasion resistance



T-01

- Anatomic insole for more comfort
- Supporting PU foam = Dissipation and Energy Return
- Fully lined with conductive micro-perforated fabric to reduce foam wearing

